

Klarion™ EGS 6020

TECHNICAL SPECIFICATIONS

	Klarion Cleaner	Klarion Sanitizer
Base System (Does not include storage tanks)	30.25" x 30.25" x 79" (77 cm x 77 cm x 200 cm)	
Functionality	Generate ECA solutions on-site	
Intended Use	Multi-purpose cleaner	Surface sanitizer
Output	1.0 - 1.5 gpm (4.0 - 5.5 lpm)	0.6 gpm (2.3 lpm)
Operating Voltage	100-240VAC, 50/60Hz, single phase	
Power Consumption	0.7 kW	
Salt Consumption (Not including water softener)	Approx 0.3 lbs/hour (0.14 kg/hr)	
Salt Purity	99.9% NaCl	
Water Hardness Requirement (Achieve with included water softener)	< 1 grain/gallon	
Iron Content Requirement	< 0.3 mg/l (ppm)	
Chemical Contents	< 0.04% Sodium Hydroxide > 99.96% Water	< 0.02% Hypochlorous Acid > 99.98% Water
pH	11 - 12.5	5 - 6
Free Available Chlorine Content	–	> 150 mg/l (ppm)



From *Spraying Systems Co.*

CONTACT US FOR MORE INFORMATION

North Avenue and Schmale Road, P.O. Box 7900, Wheaton, IL 60187-7901 USA

Tel: 1.630.517.1010

info@klarion.com

www.klarion.com