

Klarion™ EGS 6020

TECHNICAL SPECIFICATIONS

| | Klarion Cleaner | Klarion Sanitizer |
|---|--|---|
| Base System (Does not include storage tanks) | 30.25" x 30.25" x 79" (77 cm x 77 cm x 200 cm) | |
| Functionality | Generate ECA solutions on-site | |
| Intended Use | Multi-purpose cleaner | Surface sanitizer |
| Output | 1.0 - 1.5 gpm (4.0 - 5.5 lpm) | 0.6 gpm (2.3 lpm) |
| Operating Voltage | 100-240VAC, 50/60Hz, single phase | |
| Power Consumption | 0.7 kW | |
| Salt Consumption (Not including water softener) | Approx 0.3 lbs/hour (0.14 kg/hr) | |
| Salt Purity | 99.9% NaCl | |
| Water Hardness Requirement (Achieve with included water softener) | < 1 grain/gallon | |
| Iron Content Requirement | < 0.3 mg/l (ppm) | |
| Chemical Contents | < 0.04% Sodium Hydroxide > 99.96% Water | < 0.02% Hypochlorous Acid > 99.98% Water |
| pH | 11 - 12.5 | 5 - 6 |
| Free Available Chlorine Content | – | > 150 mg/l (ppm) |



From *Spraying Systems Co.*

CONTACT US FOR MORE INFORMATION

North Avenue and Schmale Road, P.O. Box 7900, Wheaton, IL 60187-7901 USA

Tel: 1.630.517.1010

info@klarion.com

www.klarion.com